

Product Description

The KBC ESMGS24-N4-RXX-B series is a high-performance, managed Gigabit switch with 24 x 802.3at PoE+ Gigabit downlink ports and 4 10G uplink SFP ports. It is designed for large-scale IP surveillance applications and networks. Each PoE port (up to 30W) satisfies a PoE IP camera's high power consumption requirement. PoE budget is up to 480W. The switch is also ideal for applications requiring Power Sourcing Equipment (PSE) functionality, such as IP switches, routers and hubs, CCTV DVR, home networking and industrial Ethernet. Automatic identification of the Powered Device (PD) maintains a reliable power supply to external devices. The switch supports rich network functionalities such as ERPS, VLAN, RSTP, rate limiting, port security, SNMP and more.




The KBC ESMGS24-N4-RXX-B Ethernet switch is available as a 1U rack unit.

Product Features

- Provide 24 PoE+ Gigabit downlink copper ports and 4 10G uplink SFP ports
- Provide web-based layer 2 network management and PoE management by simple operation
- Support IEEE802.3af&at PoE
- Support ITU-T G.8032 Ethernet ring protection, as well as STP, RSTP and MSTP
- Support Command Line Interface (CLI) for fast configuration of major management functions
- Support DHCP Option 82 for IP address assignment with different policies
- Support IGMP snooping and MLD snooping for constraining multicast traffic
- Support private VLAN and IEEE802.1Q VLAN
- Provide lock port function based on MAC address for blocking unauthorized access
- Support IEEE802.3ad LACP for optimum bandwidth utilization
- Support QoS (IEEE802.1p/1Q and TOS/DiffServ) to increase determinism
- Support TACACS+, SNMPv3, IEEE 802.1X, HTTPS, and SSH to enhance network security
- Support SNMPv1/v2c/v3 for different levels of network management
- Support RMON for efficient network monitoring and proactive capability
- Support port mirroring for online debugging
- Support high-speed data forwarding, very suitable for a large flow of video data forwarding in security surveillance
- Quick Installation, simple operation, convenient for desk or rack installation
- Optional redundant power supply

Part Number Configurator



Specifications

Specifications

IEEE Standards

IEEE802.3
IEEE802.3u
IEEE802.3z
IEEE802.3ab
IEEE802.3X
IEEE802.3ad
IEEE802.3ae
IEEE802.1Q
IEEE802.1p
IEEE802.1D
IEEE802.1X
IEEE802.1w
IEEE802.1s
IEEE802.3af&at

Ports ⁽¹⁾

10/100/1000Base-T(X) Downlink
10G SFP Uplink

RJ45 (24)
SFP (4)

PoE

Standard
PSE Type
Power Pin Assignment
PoE Power Output
PoE Budget

IEEE 802.3af/at
End-span
1/2(+), 3/6(-)
30 watts max. per port
480W max.

Switch Performance

Architecture
Capacity
Throughput
Mac Table
Memory Buffer
IGMP Group

Store-and-forward
128Gbps
42Mpps
32k
32M
1024

Layer 2 Functions

Management interface

Web-based GUI and CLI; SSH;
Telnet
SNMP v1, v2 & v3
Port enable/disable; Full duplex;
Speed configuration;
Flow control enable/disable;
Port naming
802.1Q VLAN protocol;
port-based VLAN; 4K VLAN

Port configuration

VLAN

Layer 2 Functions (cont.)

Quality of Service (QoS)

Multicasting

PoE

Security

System

QoS Congestion Management;
15 priority queues; SP, WRR and
SP+WRR queue scheduling;
802.1p CoS/DSCP priority
IGMP v1/v2/v3, IGMP snooping, and
MLI snooping
Total power control; PoE On/Off;
Output port and priority
combinations; 802.1X;
MAC address auto-learning, aging and
filtration;
Port isolation, port speed limit;
Link aggregation
TFTP/WEB load upgrade;
Traffic statistics;
MAC address table query;
IP address modifications;
Username and password
modification; History and log;
System Configuration Backup;
Recover the default factory settings

Power ⁽²⁾

Power Input
Power Consumption
Redundant Power³

100-240VAC, 50/60Hz
<30W (without PoE)
Optional

Environmental

Operating Temperature
Storage Temperature
Operating Humidity

-30 °C ~ +65 °C
-40 °C ~ +85 °C
5% to 95% non-condensing

Mechanical


Dimensions (L x W x H)
Weight

445mm x 335mm x 44mm
5.8Kg

Protection

Lightning protection
ESD

6KV Execute: IEC61000-4-5
6KV Contact discharge;
8KV Air discharge;
Execute: IEC61000-4-2



1. SFP module sold separately.

2. Please select the power plug from US Standard, Euro 2 Circular, UK 3 Pin square, or Australian when placing an order.

3. Please refer to the Part Number Configurator section for part number of switch with redundant power option.

Due to ongoing technological improvements, product specifications are subject to change without notice. KBC is not liable for errors, omissions, or changes to any description of the goods contained herein. This information is for the sole purpose of identifying the products and KBC makes no warranty that the products conform to any description contained herein. Do not rely solely on representations, statements, or assertions concerning these products.